

Material Safety Data Sheet

REVISION DATE: 06/01/2017 VERSION: 2

1. Identification of substa	nce:	
*Product details:		
Trade name: <u>TERDH-1100</u>		
*Application of the substance /	the preparation	
Preparation of: Adhesives, Coatings, Sealants, Rubber, Asphalt.		
*Manufacturer/Supplier:		
TER HONGKONG LIMITED		
Add: Room 2201, Fortress Tower, 250 Kings Road, Hong Kong		
Tel: 852 3563 8267	Fax: 852 2510 7944	
www.terhk.com.hk	Email: janet@terhk.com.hk	
2. Hazards identification		
*Hazard designation: void		
*Information pertaining to part	ticular dangers for man and environment: void	
*Classification system		
The classification is in line wit	h current EC lists. It is expanded, however, by information from	
technical literature and by information furnished by supplier companies.		
3. Composition/information on ingredients		
*Chemical characterization:		
*CAS No. Designation: 64742-16-1 Hydrocarbon resin		
*Identification number(s): none, polymer		
4. First aid measures		
*General information No special measures required.		
*After inhalation Supply fresh a	air; consult doctor on case of symptoms.	
*After skin contact: After conta	ect with the molten product, cool rapidly with cold water.	
Do not pull solidified product	away from the skin.	
*After eye contact: Rinse open	ed eye for several minutes under running water.	
If symptoms persist, consult d	loctor.	
*After swallowing: Rinse out m	outh and then drink plenty of water. Seek medical treatment.	
5. Fire fighting measures		
*Suitable extinguishing agents		
CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.		
*For safety reasons unsuitable extinguishing agents: water with a full water jet.		
*Special hazards caused by the material: its products of combustion or flue gases, formation of		
toxic gases is possible during heating or in case of fire.		
*Protective equipment: put on breathing apparatus.		
*Additional information: fire residues and extinguishing water must be disposed safety.		
6. Accidental release measures		
*Person-related safety precautions:		
Avoid causing dust. Remove all ignition sources.		

Wear protective equipment. Keep unprotected persons away.

*Measures for environmental protection:

Do not allow product to reach sewage system or water bodies.

*Measures for cleaning/collecting: collect mechanically.

7. Handling and storage

*Handling

*Information for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin and eyes.

Prevent formation of dust.

Avoid breathing dust.

Observe workplace exposure limits.

*Information about protection against explosions and fires:

Dust can combine with air to form an explosive mixture.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

*Storage: All resins with a low softening point present risk of solidifying or lump.

*Requirements to be met by storerooms and containers:

Observe all relevant storage regulations for protection of water bodies.

Keep tightly sealed in a dry,ventilated and cool place.

Keep at temperature not exceeding 25℃.

Keep far away from direct sunlight and heat sources.

Material to avoid: Strong oxidizing agents.

8. Exposure controls and personal protection

*Additional information about design of technical systems:

*Components with critical values that require monitoring at the workplace:

Observe all workplace limits for dust.

*Additional information:

The lists that were valid during the compilation were used as basis.

No further data. See item 7.

*Personal protective equipment

*General protective and hygienic measures:

Do not inhale dust/ smoke/ mist.

Avoid close or long term contact with the skin.

Avoid contact with the eyes.

Wash hands during breaks and at the end of the work.

*Breathing equipment:

Dust mask: If all applicable workplace exposure limits are observed and good ventilation is ensured, no special measures required.

*Protection of hands: Protective gloves.

*Material of gloves

The selection of the suitable gloves does not only depent on the material, but also on further marks of quality and varies from manufacturer to manufactuer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

*Penetration time of glove material

The exact break trough time has to be found out by the manufacture of the protective gloves and has to be observed.

9. Physical and chemical properties:		
*General Information		
Form:	Granular	
Colour:	Water White	
*Change in condition		
Softening Point:	100-130℃	
Boiling point/Boiling range:	not applicable	
*Flash point:	200℃(or higher)	
*lgnition temperature:	350-450℃(or higher)	
*Self-inflammability:	product is not selfigniting	
*Density at 25℃	1.03-1.13 g/cm3	
*Solubility in / Miscibility with water	insoluble	
*Danger of explosion: not explosive	e but ignitable or explosive air/ dust mixtures are possible.	
10. Stability and reactivity		
*Conditions to be avoided:		
No decomposition if used according to specifications.		
To avoid thermal decomposition do not overheat.		
*Materials to be avoided:		
Strong oxidizers		
Strong acids		
Halogens		
*Dangerous reactions: risk of dust explo	sion if enriched with fine dust in presence of air.	
*Dangerous products of decomposition: carbon monoxide and carbon dioxide, danger of toxic		
*Dangerous products of decomposition:	carbon monoxide and carbon dioxide, danger of toxic	
*Dangerous products of decomposition: pyrolysis products.	carbon monoxide and carbon dioxide, danger of toxic	
	carbon monoxide and carbon dioxide, danger of toxic	
pyrolysis products.	carbon monoxide and carbon dioxide, danger of toxic	
pyrolysis products. 11. Toxicological information		
pyrolysis products. 11. Toxicological information *Acute toxicity:		
pyrolysis products. 11. Toxicological information *Acute toxicity: *LD/LC50 values that are relevant for cla		
pyrolysis products. 11. Toxicological information *Acute toxicity: *LD/LC50 values that are relevant for cla 64742-16-1 Hydrocarbon resin		
pyrolysis products. 11. Toxicological information *Acute toxicity: *LD/LC50 values that are relevant for cla 64742-16-1 Hydrocarbon resin Oral LD50 >50000 mg/kg (rat) *Primary irritant effect:		
pyrolysis products. 11. Toxicological information *Acute toxicity: *LD/LC50 values that are relevant for cla 64742-16-1 Hydrocarbon resin Oral LD50 >50000 mg/kg (rat) *Primary irritant effect: *On the skin: Product may cause irritation	ssification:	
pyrolysis products. 11. Toxicological information *Acute toxicity: *LD/LC50 values that are relevant for cla 64742-16-1 Hydrocarbon resin Oral LD50 >50000 mg/kg (rat) *Primary irritant effect: *On the skin: Product may cause irritation	ssification: on mechanically due to its content of fine dust. n mechanically due to its content of fine dust.	
pyrolysis products. 11. Toxicological information *Acute toxicity: *LD/LC50 values that are relevant for cla 64742-16-1 Hydrocarbon resin Oral LD50 >50000 mg/kg (rat) *Primary irritant effect: *On the skin: Product may cause irritatio *On the eye: Product may cause irritatio	ssification: on mechanically due to its content of fine dust. n mechanically due to its content of fine dust.	
pyrolysis products. 11. Toxicological information *Acute toxicity: *LD/LC50 values that are relevant for cla 64742-16-1 Hydrocarbon resin Oral LD50 >50000 mg/kg (rat) *Primary irritant effect: *On the skin: Product may cause irritatio *On the eye: Product may cause irritatio *Sensitization: No sensitizing effect know *Additional toxicological information:	ssification: on mechanically due to its content of fine dust. n mechanically due to its content of fine dust.	
pyrolysis products. 11. Toxicological information *Acute toxicity: *LD/LC50 values that are relevant for cla 64742-16-1 Hydrocarbon resin Oral LD50 >50000 mg/kg (rat) *Primary irritant effect: *On the skin: Product may cause irritatio *On the eye: Product may cause irritatio *Sensitization: No sensitizing effect know *Additional toxicological information:	ssification: on mechanically due to its content of fine dust. n mechanically due to its content of fine dust. wn.	
pyrolysis products.11. Toxicological information*Acute toxicity:*LD/LC50 values that are relevant for cla64742-16-1 Hydrocarbon resinOral LD50 >50000 mg/kg (rat)*Primary irritant effect:*On the skin: Product may cause irritation*On the eye: Product may cause irritation*Sensitization: No sensitizing effect know*Additional toxicological information:When used and handled according to specific text	ssification: on mechanically due to its content of fine dust. n mechanically due to its content of fine dust. wn.	
pyrolysis products. 11. Toxicological information *Acute toxicity: *LD/LC50 values that are relevant for cla 64742-16-1 Hydrocarbon resin Oral LD50 >50000 mg/kg (rat) *Primary irritant effect: *On the skin: Product may cause irritatio *On the eye: Product may cause irritatio *Sensitization: No sensitizing effect know *Additional toxicological information: When used and handled according to sp according to our experience and the info	ssification: on mechanically due to its content of fine dust. n mechanically due to its content of fine dust. wn. pecifications, the product does not have any harmful effects ormation provided to us.	
pyrolysis products.11. Toxicological information*Acute toxicity:*LD/LC50 values that are relevant for cla64742-16-1 Hydrocarbon resinOral LD50 >50000 mg/kg (rat)*Primary irritant effect:*On the skin: Product may cause irritation*On the eye: Product may cause irritation*Sensitization: No sensitizing effect know*Additional toxicological information:When used and handled according to spaceording to our experience and the info12. Ecological information:	ssification: on mechanically due to its content of fine dust. n mechanically due to its content of fine dust. wn. pecifications, the product does not have any harmful effects ormation provided to us.	
pyrolysis products.11. Toxicological information*Acute toxicity:*LD/LC50 values that are relevant for cla64742-16-1 Hydrocarbon resinOral LD50 >50000 mg/kg (rat)*Primary irritant effect:*On the skin: Product may cause irritation*Sensitization: No sensitizing effect know*Additional toxicological information:When used and handled according to spaceording to our experience and the info12. Ecological information:*Information about elimination (persistential structure)*Other information: the product is slight	ssification: on mechanically due to its content of fine dust. n mechanically due to its content of fine dust. wn. pecifications, the product does not have any harmful effects ormation provided to us.	
pyrolysis products.11. Toxicological information*Acute toxicity:*LD/LC50 values that are relevant for cla64742-16-1 Hydrocarbon resinOral LD50 >50000 mg/kg (rat)*Primary irritant effect:*On the skin: Product may cause irritation*Sensitization: No sensitizing effect know*Additional toxicological information:When used and handled according to spaccording to our experience and the info12. Ecological information:*Information about elimination (persistent*Other information: the product is slight	ssification: on mechanically due to its content of fine dust. n mechanically due to its content of fine dust. wn. pecifications, the product does not have any harmful effects ormation provided to us. nce and degradability): ly biodegradable.	
pyrolysis products.11. Toxicological information*Acute toxicity:*LD/LC50 values that are relevant for cla64742-16-1 Hydrocarbon resinOral LD50 >50000 mg/kg (rat)*Primary irritant effect:*On the skin: Product may cause irritation*Sensitization: No sensitizing effect know*Additional toxicological information:When used and handled according to spaceording to our experience and the info12. Ecological information:*Information about elimination (persistential source)*Other information: the product is slight*General notes: Water hazard class 1 (Set	ssification: on mechanically due to its content of fine dust. n mechanically due to its content of fine dust. wn. pecifications, the product does not have any harmful effects ormation provided to us. nce and degradability): ly biodegradable.	
pyrolysis products.11. Toxicological information*Acute toxicity:*LD/LC50 values that are relevant for cla64742-16-1 Hydrocarbon resinOral LD50 >50000 mg/kg (rat)*Primary irritant effect:*On the skin: Product may cause irritation*On the eye: Product may cause irritation*Sensitization: No sensitizing effect know*Additional toxicological information:When used and handled according to spaceording to our experience and the info12. Ecological information:*Information about elimination (persistential structure)*Other information: the product is slight*General notes: Water hazard class 1 (Se13. Disposal considerations	ssification: on mechanically due to its content of fine dust. n mechanically due to its content of fine dust. wn. pecifications, the product does not have any harmful effects ormation provided to us. nce and degradability): ly biodegradable.	

Do not allow product to reach sewage system.

*Uncleaned packagings:

*Recommendation: Disposal according to offical regulations.

14. Transport information

*Land transport ADR/RID and GGVS/GGVE (cross-border/domestic)

*ADR/RID-GGVS/E Class:-

*Maritime transport IMDG/GGVSea:

*IMDG/GGVSea Class: -

*Air transport ICAO-TI and IATA-DGR:

*ICAO/IATA Class: -

*Transport/Additional information: no dangerous good according to the above specifications.

15. Regulatory information

*Designation according to EC guidelines:

Observe the normal safety regulations when handling chemicals.

The products has not been classified and labelled in accordance with EC directives / relevant national laws.

*National regulations

*Water hazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

Water hazard classification was done according to the precondition of the VwVwS from 27-07-2005.

16. Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.